

# DBF110 Series

## Dryer Booster Fans

### Description

A integral centrifugal fan and positive pressure sensing switch specifically designed for residential dryer vent booster applications. The fan can be mounted in any angle at any point along the duct work and straight-through air flow design allows easy installation. By using using accessory FC mounting clamps, fan can easily be removed from duct work for service. Fan inlet and outlet are 3 7/8" diameter allowing direct installation into dryer vent duct thereby eliminating the need for transition pieces. Motor bearings are a permanently sealed, self lubricating ball type. DBF110 fan is backed by Fantech's Five Year Warranty.

### Installation Notes:

1. For maximum sensitivity, switch diaphragm must be mounted vertically. Failure to orient the diaphragm vertically may result in improper operation
2. Fan must be mounted a minimum of 15 linear (not equivalent) feet from the dryer in order to prevent the impeller from loading with wet lint. If mounted within 15 feet, an accessory, secondary lint trap (DBLT 4W) must be used. (see installation manual)
3. Fan should be inspected periodically, depending on amount of usage, and cleaned as necessary

### Guide Specifications for Model DBF110 Dryer Vent Booster System

Inline fan shall be of the centrifugal, direct driven type

### Construction

#### Housing

- Fan housing shall be constructed of UV resistant ABS-PC blended thermoplastic
- Fan shall be supplied with an integral external electrical terminal box with pre-wired terminal strip connections
- Capacitor shall be provided and shall be located within the fan electrical terminal box

#### Motor

- Motorized impeller shall be an external rotor type, class B insulation, totally enclosed permanent split capacitor type
- Motor shall be a permanently sealed self lubricating ball bearing type
- Motor shall be equipped with automatic reset thermal overload protection
- Motor shall be acceptable for continuous duty

#### Wheel

- Fan wheel shall be of the backward inclined centrifugal type with an inlet venturi for maximum performance
- Motorized impeller shall be both statically and dynamically balanced as one integral unit to provide for vibration free performance

#### Switch

- Integral positive pressure switch shall be mounted on the fan and prewired to the terminal strip provided in fan electrical junction box
- Switch shall be set to 0.05" H<sub>2</sub>O<sub>g</sub> static pressure
- Switch shall incorporate a delay-on-break timer cycle to maintain fan performance for intervals of 10 minutes until drying cycle is complete

### Code Approval

- Fan shall be certified by ETL to the UL507 standard for safety
- Rating shall include approval for residential dryer exhaust and air stream temperatures not to exceed 140°F (60°C)

DBF110 Series shall be manufactured under the authority of Fantech, Inc., Lenexa, KS.

**United States** 10048 Industrial Blvd. • Lenexa, KS 66215 • 1.800.747.1762 • [www.fantech.net](http://www.fantech.net)

**Canada** 50 Kanalfakt Way • Bouctouche, NB E4S 3M5 • 1.800.565.3548 • [www.fantech.net](http://www.fantech.net)

Fantech reserves the right to make technical changes.

For updated documentation please refer to [www.fantech.net](http://www.fantech.net)

